

FRIENDLY™ SHOWERS & TUB/SHOWERS

H 44 B (RH) | H 45 B (LH)

Unit Outside Dimensions: 60" x 32 1/2" x 74"

Inside Tub Dimensions:

Top of well: 52 1/2" x 23 1/4"

Bottom of well: 44" x 19"

Apron Height: 15"

Door Opening: 57" x 57"

Shipping weight: starting at 125 lbs.

Features:

- Reinforced for the future installation of grab bars and fold-up seat
- 15" outside Apron Height
- Flat walls for easy grab bar positioning and fold-up seat installation
- Acrylic grab bar
- Wood reinforcement for shower door or curtain rod brackets
- Textured floor - meets and exceeds ASTM F-462 slip resistance standard
- Boot Print balsa wood base

Options:

See page 24 for standard packages and options. See page 66 for accessory options that include collapsible dam, end caps, soap dishes, curtain rod, grab bars and fold-up seats.



H 248 B

Unit Outside Dimension: 48" x 36" x 79"

Inside Dimension: 44" x 29"

Front Outside Threshold height: 3"

Inside dam height: 1 3/4"

Door Opening: 41 7/8" x 74"

Shipping weight starting at: 135 lbs.

Features:

- Reinforced for the future installation of grab bars and a fold-up seat
- Flat walls for easy grab bar positioning at 34" above the floor
- Reinforced pillars for shower door or curtain rod support
- No seat for extremely spacious 48" x 36" shower
- Textured floor - meets and exceeds ASTM F-462 slip resistance standard
- Front-Fit™ remodeling shower

Options:

See page 24 for standard packages and options. See page 66 for accessory options that include collapsible dam, end caps, soap dishes, curtain rod, grab bars and fold-up seats.

