

FRIENDLY™ SHOWERS & TUB/SHOWERS

H 533 A FF

Unit Outside Dimension: 60" x 30" x 80 ½"

Inside Dimension: 55" x 22"

Front Outside Threshold height: 3"

Inside dam height: 1 ½"

Door Opening: 56 ¾" x 76"

Shipping weight starting at: 150 lbs.



Features:

- Designed to replace existing cast iron tubs, steel tubs, and tub/shower modules
- Reinforced for the future installation of grab bars and fold-up seat
- NO seat for Spacious 30" shower
- Low 3" front outside threshold for easy entry
- 1 ½" inside dam to contain water
- Flat walls for easy grab bar positioning at 34" (ADA height) above the floor and for vertical grab bar on either side wall
- Textured floor - meets and exceeds ASTM F-462 slip resistance standard

Options:

See page 24 for standard packages and options. See page 66 for accessory options that include collapsible dam, end caps, soap dishes, curtain rod, grab bars and fold-up seats.



H 852 A (RH) - Left Seat

H 853 A (LH) - Right Seat

Unit Outside Dimensions: 48" x 36" x 79"

Inside Dimension: 41" x 29"

Front Threshold Height: 4 ½"

Inside dam: 3"

Seat Height: 17"

Door Opening: 40" x 72 ¾"

Shipping weight: starting at 140 lbs.

Features:

- Base unit is reinforced for the future installation of grab bars
- Low front threshold for easy entrance and exit
- Large Integral contoured seat
- Reinforced pillars for shower door or curtain rod support
- Textured floor - meets and exceeds ASTM F-462 slip resistance standard
- Boot Print balsa wood base

"A" package includes: One 12" horizontal grab bar on back wall and one 24" vertical grab bar on wet wall

Options:

See page 24 for standard packages and options. See page 66 for accessory options that include collapsible dam, end caps, soap dishes, curtain rod, grab bars and fold-up seats.

