
FRONT-FIT™ REMODELING SHOWERS



Unit Dimensions: 60" x 30" x 80 ½"
Inside Shower Dimensions: 56 ½" x 24"

Door Opening: 56 ¾" x 76" Front Threshold Height: 3" Shipping Weight: 150 lbs.

Features:

- Designed to replace existing cast iron/steel tubs or tub/shower modules
- Front-Fit remodeling system for easy installation
- Low 3" outside front threshold for easy step over
- Large seat
- Twin corner shelves
- Unit is grab bar friendly
- Wood reinforcement for shower door or curtain rod brackets
- Shower door is recommended
- Textured floor meets and exceeds ASTM F-462 slip resistance standard

Options:

Custom backing for grab bars, T-53 dome, and dome light



WR 533 FF

Unit Outside Dimension: 60" x 30" x 80 1/2"

Inside Dimension: 55" x 22"
Front Outside Threshold height: 3"

Inside dam height: 1 ½"
Door Opening: 56 ¾" x 76"

Shipping weight starting at: 150 lbs.

Features:

- Designed to replace existing cast iron tubs, steel tubs, and tub/shower modules
- No seat for Spacious 30" shower
- Low 3" front outside threshold for easy entry
- 1 ½" inside dam to contain water
- Textured floor meets and exceeds ASTM F-462 slip resistance standard
- Flat walls for easy grab bar positioning at 34" (ADA height) above the floor and for vertical grab bar on either side wall
- See Supplimental List Price Sheet for A (grab bars,) B (grab bars and fold up seat), and C (complete package) package options

Options:

Custom backing for grab bars, fold-up seat, WR-T53 dome and dome light



