





Warm Rain models WR 900 (right hand) and WR 901 (left hand) tub/shower fixtures are constructed of reinforced polyester resin covered with a high gloss .187 acrylic sheet. The reinforced fiberglass has a minimum content of 18 % fiberglass.

The bottom base of the unit is constructed of 1/2" end-grained balsa wood sandwiched between 2 layers of reinforced fiberglass. The base is an integral part of the unit.

The inside bottom floor will be textured. The texture bottom floor meets and exceeds ASTM Safety Specification F-462.

The unit will measure 60" x 33" x 88" and has a 16.5" apron height. The inside dam will measure 13.50" and the overflow will be 13" above the floor.

The inside sump area will measure 56" x 24" at the top of the well and 42" x 21" at the bottom of the well.

The front apron of all units will have wood support along the entire length to help prevent the corners from chipping or bowing in or out.

The WR 900 and WR 901 will have wood support for a shower door and a curtain bracket. These units have the option of being reinforced for the future installation of grab bars and the above floor rough-in.


These Warm Rain tub/showers arrive on site fully tested, inspected, and certified to meet or exceed the precise standards established by FHA/HUD, materials bulletin 73, American National Standards Z-124.1 and Z-124.2, ASTM/E-84.

Warm Rain Corporation, 51675 N. Industrial Drive, Calumet, MI 49913


Voice: 906-482-3750 Fax: 906-482-2585 email: <u>tedk@warmrain.com</u> website: <u>www.warmrain.com</u>


Page 1 of 2





WR 900/1





5-15-12

